

Ares

Balanced rolling
Doors



Ares electromechanical gear motor for balance rolling doors (max 170Kg)
Is available in 230Vac version.

230V



Adapter



Electrobrake

Technical data

	Ares 60	Ares 60/S
Power supply	230V~ /50 Hz	230V~ /50 Hz
Max. input power	1,8A	2,4A
Motor power supply	230V ~	230V ~
Max. motor power	330W	450W
Working temperature (°C)	-20°< >+60°	-20°< >+60°
Max. travel time (Tw)	4min	4min
Thrust force	140Kg	170Kg
Torque	140Nm	190Nm
Rolling shutter diameter	60mm	60mm
Spring holding box diameter	200mm	200mm

Irreversible electromechanical gearmotor for balanced rolling doors max 170Kg



AA142300000

Ares 230Vac gearmotor with lifting capacity till 140Kg.

AA142310000

Ares 230Vac gear motor with lifting capacity till 140Kg, complete with electrobrake to get it irreversible.

AA172300000

Ares 230Vac gearmotor with lifting capacity till 170Kg.

AA172310000

Ares 230Vac gear motor with lifting capacity till 170Kg, complete with electrobrake to get it irreversible.



Accessories



AA006

Shaft reduction 60/42.



AA007

Shaft reduction 60/48.



AA008

Expansion fitter from $\varnothing 200$ to $\varnothing 220$.



AA009

Optional electrobrake.



Push-button

See page 63.



AA2041

Control board complete with fix code receiver for Ares 230Vac motors. For control board characteristics, see page 70.



CAR

Warning notice (specify the required language).



AZ442

Zeus transmitter, 4 fix code clonable channels.